

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number  
WO 2004/028793 A1

(51) International Patent Classification<sup>7</sup>: B31C 1/00, 3/00

(21) International Application Number:

PCT/IT2003/000459

(22) International Filing Date: 25 July 2003 (25.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

FI2002A000181 26 September 2002 (26.09.2002) IT

(71) Applicant and

(72) Inventor: PERINI, Fabio [IT/IT]; Via S.Francesco, 1,  
I-55049 Viareggio (IT).

(74) Agent: MARTINI, Lazzaro; Studio Brevetti, Ing. Dr.  
Lazzaro Martini S.R.L., Via dei Rustici 5, I-50122 Firenze  
(IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS FOR FEEDING PAPER WEBS AND THE LIKE, FOR THE PRODUCTION OF CARDBOARD TUBES



(57) Abstract: Apparatus for feeding paper webs and the like, for producing cardboard tubes, characterized in that it comprises a plan modular structure (1) with a development mostly longitudinal and exhibiting two opposite surfaces (1a, 1b), one (1a) of said surfaces supporting pairs of shafts or axes (2, 2') horizontally oriented parallel to said one surface and located at a preset distance from the ground, each of said shafts or axes (2, 2') intended to support at least a reel (3, 3') from which a paper web unwinds, so that the output webs run parallel and superimposed to each other along the other surface (1b) of the structure, and in that it comprises automatic means, associated with said structure (1), for the cutting and mutual gluing of the webs which unwind from two different reels (3, 3') of a same pair of shafts (2, 2').

Best Available Copy

**TITLE:** "Apparatus for feeding paper webs and the like, for the production of cardboard tubes"

**SPECIFICATION**

The present invention refers to an apparatus for feeding  
5 paper webs and the like for the production of cardboard tubes.

A technique commonly adopted for the production of cardboard tubes is one making use of tube-forming machines provided with a spindle on which there are wound - to form a series of  
10 spirals being superimposed and offset of a predetermined pitch - a plurality of webs of paper or similar material suitably glued in correspondence of a surface intended to result in facing relationship to the spindle. The gluing is not operated on the first web of the series, as it is  
15 intended to directly make contact with the spindle. The motion of the webs is ensured by a belt wound around the spindle which, in addition, causes the rotation and the advancement of the tube under formation with respect to the spindle's longitudinal axis.

20 A tube-forming machine so constructed and operating is described in WO 95/10400 and WO 95/10399.

The webs, being spirally superimposed and mutually glued to form the tube, unwind from corresponding feeding reels.

Each of said reels is mounted on a corresponding support  
25 associated with means for gluing the respective web. A plurality of supports, independent from each other, are mounted in such a way as to form in their entirety a kind of fan-like figure, so that each web is directed towards the spindle of the tube-forming machine according to a  
30 corresponding angle of incidence. In relation to this, the devices presently known for supplying webs to tube-forming machines are relatively bulky, take up excessive space and

force the webs to run along cross routes and in different planes, thereby contributing to a poorly rational exploitation of the available spaces at the production site.

The main object of the present invention is to overcome the said drawbacks.

This result has been achieved, according to the invention, by adopting the idea of making an apparatus having the characteristics disclosed in the claim 1. Further characteristics being set forth in the dependent claims.

The present invention makes it possible to exploit the available spaces and reduce the overall cost of the plant. Besides, it allows making an auxiliary structure which facilitates the handling and fixing of the reels onto the respective support axes.

These and other advantages and characteristics of the invention will be best understood by anyone skilled in the art from a reading of the following description in conjunction with the attached drawings given as a practical exemplification of the invention, but not to be considered in a limitative sense, wherein:

- Fig. 1 is a schematic view in perspective of an apparatus according to the invention;

- Fig. 2 is a front view of an apparatus according to the invention;

- Fig. 3 is a rear view of the apparatus of Fig. 2;

- Fig. 4 is a plan view of the apparatus shown in Figs. 2 and 3;

- Fig. 5 shows schematically the combination of an apparatus according to the invention with a tube-forming machine (T).

Reduced to its basic structure, and reference being made to the figures of the attached drawings, an apparatus according to the invention comprises a plan structure (1) having a

development mostly longitudinal and which exhibits two opposite surfaces (1a, 1b). In correspondence of the first surface (1a), the structure (1) supports pairs of rotating shafts or axes (2, 2') horizontally oriented parallel to the same surface (1a).

Each of said shafts (2, 2') is intended to support a corresponding reel (3, 3') from which a web (N1, N2, N3; N1', N2', N3') of paper material or the like can unwind to supply a tube-making machine (T).

Because of the said disposition of the axes for supporting the reels (3, 3'), these result parallel to each other, disposed vertically and oriented orthogonal to surface (1a) of structure (1).

The axes (2, 2') of each pair of reels (3, 3') are coaxial and independent from each other, so that the rotation of a shaft (2, 2') - that is, of a reel (3, 3') - does not imply automatically the rotation of the other shaft (2, 2') of the pair - that is, of the other reel (3', 3).

The tube-forming machine (T) may be of a type known to those skilled in the art and, therefore, will not be described in further details.

The structure (1) is provided, in correspondence of its lower base, with a plurality of slits or windows (10) through which the webs unwinding from reels (3, 3') can pass from the side of the first surface (10) to the side of the second surface (1b).

On the side of the second structure (1b), the structure (1) supports a plurality of rollers (4) for guiding and tensioning the webs (N1, N2, N3) fed to the tube-forming machine (T).

In correspondence of the terminal side of structure (1), that is, on the exit side of webs fed to the tube-forming machine,

the structure (1) has a plurality of tanks (5) holding liquid glue to be used for gluing the ventral (facing downwards) part of all the webs, with the exception of the one intended to make direct contact with the spindle of the tube-forming machine. In practice, if "n" indicates the number of webs, the number of tanks (5) will be "n-1".

The webs to be glued transit above the tanks (5), in correspondence of which there are provided suitable rollers and gluing means (50). The rollers are associated with relevant actuators (51) engaged with the surface (1a) of structure (1) and by means of which the webs (N2; N3) can be moved close to or away from the respective glue-feeding means. The web intended to make direct contact with the spindle of the tube-forming machine being indicated by (N1).

Fig. 3 shows a reservoir (52) and a pump (53) for feeding glue to the tank (5). This web-gluing system is known per se to those skilled in the art.

As illustrated in Figs. 2 and 4, the webs moving towards the tube-forming machine run parallel and superimposed along the second surface (1b) of the structure (1) and up to the tube-forming machine (without engaging fan-like trajectories as it occurs, instead, with the conventional devices), which allows exploiting more effectively the available spaces and orienting the structure more conveniently with respect to the tube-forming machine.

Moreover, the shape of said structure (1) allows utilizing an auxiliary structure (6) mounted on that side in correspondence of which there are provided the shafts (2, 2') for reels (3, 3') and comprising a horizontal crosspiece (60) mounted, at a preset level from the ground, onto more supports (61) and intended to act as a guide/support for a motor-driven elevator (62) which, in turn, is mounted for

sliding on the same crosspiece (61). The elevator (62) can be suitably used (operated by a remote control not shown in the drawings but known per se) to lift the reels (3, 3') from the ground and keeping them suspended upon the positioning thereof on axes (2, 2').

Associated with the structure (1) are automatic means for unreeling the webs without interrupting the relevant flow toward the tube-forming machine (T) when one of the reels (3, 3') runs out of paper material.

Shown in the illustrative diagrams of Figs. 2, 5, 6, 7, 8 and 9 is an automatic device for cutting and gluing the webs in a manner so-called "in full flight", which actually allows feeding the webs with continuity without interrupting the flow thereof toward the tube-forming machine (T) when one of the two reels of each module runs out of paper material. Such apparatus, being provided on each module of the structure, that is, for each pair of reels (3, 3') comprises, located under two web-guiding rollers (4), an operating unit with a presser cylinder (7) orthogonally oriented to the direction in which the webs unwind, a blade (8) associated with a relevant actuator (80) for cutting the webs and located above the presser cylinder (7) and, intermediate between the presser cylinder (7) and the actuator (80) of blade (8), a flexible lamina (9) intended to maintain the head of the other web adherent upon a fixed guiding surface (90). When one reel (for example, the reel of web N1) is about to run out of material (which is sensed by a corresponding photocell located close to the same reel at a preset distance from the relevant axis 2 and supported by a fixed part of the structure), the presser (7) is automatically operated after a predetermined time. An operator will have glued beforehand a piece of both-sides-adhesive tape (91) on the head of a

stand-by web (N1'), so that the actuation of the presser (7) causes the gluing of the reeling off web (N1) on the adhesive tape attached on the head of the stand-by web (N1'). In this regard, it should be noted that both webs (N1, N1') result  
5 between said surface (90) and the presser (7). Approximately at the same time, the actuator (80) is started for cutting the reeling off web (N1) and, thereafter, the presser (7) and actuator (80) are brought back in their initial conditions (as shown in Fig. 6). In this way, the flow of webs toward  
10 the tube-forming machine (T) never stops. When the web (N1') is fully reeled off, the same operation will be performed on the head of the successive stand-by web (N1) after attaching the adhesive tape (91) (and having provided, of course, for replacing the corresponding reel in the meantime), as  
15 illustrated in the schematic diagrams of Figs. 8 and 9. In order to keep the web (N1) in stand-by condition, it can be used the same reel above described (9) which retains the head of web (N1) adherent to a fixed surface (99) located in front of the said fixed surface (90).

20 A structure according to the invention allows also using, for each module, that is, for each of the webs fed to the tube-forming machine (T), a device for controlling the tension of the webs. Such device, according to the example illustrated in Fig. 10, comprises a plate (100) mounted on two vertical  
25 guiding rails (101) and provided with two rollers (44) for the guide of a corresponding web in cooperation with the other fixed rollers (4) of the system. The said plate is engaged on top with the rod of a pneumatic cylinder (110) having dual (lower/upper) chamber, so that the position of  
30 the plate (100) corresponds to that of the rod of cylinder (110). The lower chamber of the cylinder (110) is supplied with compressed air via a controller (300) which allows

adjusting the resistance to the lowering of the plate (100) engaged with the rod of cylinder (110). The upper chamber of the latter is pneumatically connected to two pneumatic grippers (400) each of which acts on a corresponding disc (401) keyed on the axis (2) of reels (3, 3') of the structure's module associated with the device.

During operation, the diameter of the reel (3, 3') becomes smaller and smaller and, since the tension applied on the respective web (N1) is constant and corresponds to the return action operated by the tube-forming machine (T), the plate (100) tends to come down by driving along with it the rod of cylinder (110) and, thereby, increasing the volume of the upper chamber of the latter. This brings about a reduction of the pressure exerted on the grippers (400) and, accordingly, a gradual reduction of the braking action applied on the discs (401) of axis (2). In this way, practically, the tension of the web is kept constant in the portion between the respective reel and the tube-forming machine also when the diameter of the reel becomes smaller and smaller.

Practically, (all) the construction details may vary in any equivalent way as far as the shape, dimensions, elements disposition, nature of the used materials are concerned, without nevertheless departing from the scope of the adopted solution idea and, thereby, remaining within the limits of the protection granted to the present patent for industrial invention.



## CLAIMS

- 1) Apparatus for feeding paper webs and the like, for producing cardboard tubes, characterized in that it comprises a plan modular structure (1) with a development mostly longitudinal and exhibiting two opposite surfaces (1a, 1b), one (1a) of said surfaces supporting pairs of shafts or axes (2, 2') horizontally oriented parallel to said one surface and located at a preset distance from the ground, each of said shafts or axes (2, 2') intended to support at least a reel (3, 3') from which a paper web unwinds, so that the output webs run parallel and superimposed to each other along the other surface (1b) of the structure, and in that it comprises automatic means, associated with said structure (1), for the cutting and mutual gluing of the webs which unwind from two different reels (3, 3') of a same pair of shafts (2, 2').
- 2) Apparatus according to claim 1, characterized in that the said structure (1) has a plurality of slits or windows (10) through which the said webs can pass from the side of a surface (1a) to the side of the other surface (1b).
- 3) Apparatus according to one or more preceding claims, characterized in that it comprises means associated with said structure (1) for guiding said webs.
- 4) Apparatus according to one or more preceding claims, characterized in that it comprises means associated with said structure (1) for the ventral gluing of a portion of said webs.
- 5) Apparatus according to one or more preceding claims, characterized in that it comprises means for adjusting the tension of the webs which run along said surface opposite to that (1a) that supports the said shafts (2).




Fig. 1




Fig. 2




Fig. 3




Fig. 4






Fig. 5



**Fig. 6**



**Fig. 7**






Fig. 8




Fig. 9




Fig. 10

# INTERNATIONAL SEARCH REPORT

International application No  
PCT/13/00459

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 B31C1/00 B31C3/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B31C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)  
EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 882 287 A (KUCKHERMANN GUSTAV) 16 March 1999 (1999-03-16) the whole document ---	1-5
A	US 4 395 253 A (GOODMAN JAMES A) 26 July 1983 (1983-07-26) abstract; figures 1,7 ---	1-5
A	FR 2 734 757 A (TUBETTI ANTONIO FAVRETTO SRL F) 6 December 1996 (1996-12-06) abstract; figure 1 ---	1-5
A	FR 2 606 706 A (PAPER SA) 20 May 1988 (1988-05-20) the whole document ---	1-5
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

18 November 2003

Date of mailing of the international search report

02/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Damiani, A

## INTERNATIONAL SEARCH REPORT

Internatio  
PCT/ application No  
3/00459

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 937 918 A (ANACONDA ALUMINUM CO) 25 September 1963 (1963-09-25) abstract; figures 1,2 -----	1-5

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No  
PCT/73/00459

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5882287	A	16-03-1999	DE 4401723 A1 CA 2140501 A1 CN 1127178 A , B DE 59406675 D1 EP 0664208 A2 ES 2119052 T3 JP 3345201 B2 JP 8025527 A RU 2095250 C1 TW 417600 Y	27-07-1995 22-07-1995 24-07-1996 17-09-1998 26-07-1995 01-10-1998 18-11-2002 30-01-1996 10-11-1997 01-01-2001
US 4395253	A	26-07-1983	US 4250797 A US 4347934 A	17-02-1981 07-09-1982
FR 2734757	A	06-12-1996	IT T0950128 U1 FR 2734757 A1	02-12-1996 06-12-1996
FR 2606706	A	20-05-1988	ES 2008113 A6 FR 2606706 A1 IT 1223080 B	16-07-1989 20-05-1988 12-09-1990
GB 937918	A	25-09-1963	FR 1303827 A US 3156401 A DE 1411533 A1	14-09-1962 10-11-1964 17-10-1968

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**